


技术指标

@T_A=25±2℃ 无特别规定时


项目		单位	最小值	典型值	最大值
中心频率		MHz	-	1240.00	
最小插入损耗		dB	-	1.9	2.2
插入损耗	1230.00-1250.00MHz	dB	-	1.9	2.5
带内波动	1230.00-1250.00MHz	dB	-	0.5	1.0
群时延波动	1230.00-1250.00MHz	ns	-	10.0	40.0
输入输出驻波比	1230.00-1250.00MHz	ratio	-	1.7:1	2.0:1
阻带抑制	0.300-1100.00MHz	dB	55.0	60.0	-
	1100.00-1174.00MHz		55.0	60.0	-
	1174.00-1195.00MHz		10.0	15.0	-
	1195.00-1200.00MHz		5.0	15.0	-
	1281.00-1315.00MHz		15.0	25.0	-
	1315.00-1363.00MHz		40.0	45.0	-
	1363.00-2500.00MHz		40.0	45.0	-
	2500.00-3000.00MHz		30.0	35.0	-
相位一致性		deg.	-		
幅度一致性		dB	-		
输入输出阻抗		Ω	50		
最大输入功率		dBm	20		
工作温度		℃	-40 ~ +85		
存储温度		℃	-40 ~ +85		
材料		-			
RoHS		-	是		
静电敏感器件		-	是		
防潮等级		-	MSL 1		
订单数量		pcs	20		3000


外形结构




丝印说明	散货打标方式	整卷打标方式
	中心频率: xxxxx	型号: SAWxxxx
	Pin 1: ●	Pin 1: ●
	-	批次号: 月年日, 如: 04B22


测试电路







频率特性





卷盘尺寸





推荐回流焊炉温曲线图

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

